sigma-aldrich.com

SAFETY DATA SHEET

Version 4.9 Revision Date 09/23/2016 Print Date 05/15/2018

1. PRODUCT AND COMPANY IDENTIFICATION

| 1.1 | Product identifiers Product name | [:] 2-Butanone | |
|-----|-------------------------------------|-------------------------|--|
| | Product Number Brand | : 48877 : Supelco | |
| | CAS-No. | : 78-93-3 | |
| | | | |

1.2 Relevant identified uses of the substance or mixture and uses advised against

| Identified uses : Laboratory chemicals, Synthesis of substances | dentified uses | : Laboratory chemicals, Synthesis of substances |
|-----------------------------------------------------------------|----------------|-------------------------------------------------|
|-----------------------------------------------------------------|----------------|-------------------------------------------------|

1.3 Details of the supplier of the safety data sheet

| Company | : | Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA |
|------------------|---|--------------------------------------------------------------------|
| Telephone Fax | : | +1 800-325-5832 +1 800-325-5052 |
| | | |

1.4 Emergency telephone number

| Emergency Phone # | : | +1-703-527-3887 (| (CHEMTREC) |) |
|-------------------|---|-------------------|------------|---|
|-------------------|---|-------------------|------------|---|

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Acute toxicity, Oral (Category 3), H301 Acute toxicity, Inhalation (Category 3), H331 Acute toxicity, Dermal (Category 3), H311 Specific target organ toxicity - single exposure (Category 1), H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word



Danger

| Hazard statement(s) H225 H301 + H311 + H331 H370 | Highly flammable liquid and vapour. Toxic if swallowed, in contact with skin or if inhaled Causes damage to organs. |
|--------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Precautionary statement(s) P210 P233 P240 P241 P242 | Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. |

| P243 | Take precautionary measures against static discharge. |
|--------------------|------------------------------------------------------------------------------------------------------------|
| P260 | Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. |
| P264 | Wash skin thoroughly after handling. |
| P270 | Do not eat, drink or smoke when using this product. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves/ eye protection/ face protection. |
| P301 + P310 + P330 | IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth. |
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304 + P340 + P311 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor. |
| P307 + P311 | IF exposed: Call a POISON CENTER or doctor/ physician. |
| P362 | Take off contaminated clothing and wash before reuse. |
| P370 + P378 | In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. |
| P403 + P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403 + P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |
| P501 | Dispose of contents/ container to an approved waste disposal plant. |

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

| Synonyms | : Methyl ethyl ketone MEK Ethyl methyl ketone |
|------------------|------------------------------------------------------------------|
| Formula | : C ₄ H ₈ OC ₄ H ₈ O |
| Molecular weight | : 72.11 g/mol |

Hazardous components

| Component | | Classification | Concentration |
|---------------------|-----------------------|-----------------------------|----------------|
| Methanol | | | |
| CAS-No. | 67-56-1 | Flam. Liq. 2; Acute Tox. 3; | >= 70 - < 90 % |
| EC-No. | 200-659-6 | STOT SE 1; H225, H301 + | |
| Index-No. | 603-001-00-X | H311 + H331, H370 | |
| Registration number | 01-2119433307-44-XXXX | | |

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

| Component | CAS-No. | Value | Control parameters | Basis |
|-----------|---------|---------------------------------|--------------------|--------------------------------------------|
| Methanol | 67-56-1 | TWA | 200.000000 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| | Remarks | Headache Nausea Dizziness | | |

| Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) | | |
|---------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|----------------------------------------------------------------------------------------|
| Danger of cu | utaneous absorptio | n |
| STEL | 250.000000 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| (see BEI® se Danger of cu | for which there is a ection) <u>utaneous absorptio</u> | |
| TWA | 200.000000 ppm 260.000000 mg/m3 | USA. NIOSH Recommended Exposure Limits |
| Potential for | dermal absorption | |
| ST | 250.000000 ppm 325.000000 mg/m3 | USA. NIOSH Recommended Exposure Limits |
| Potential for | dermal absorption | |
| TWA | 200.000000 ppm 260.000000 mg/m3 | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| The value in | mg/m3 is approxir | mate. |
| TWA | 200 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) | | |
| STEL | itaneous absorptio 250 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| (see BEI® se | for which there is a | a Biological Exposure Index or Indices |
| TWA | 200 ppm 260 mg/m3 | USA. NIOSH Recommended Exposure Limits |
| Potential for | dermal absorption | |
| ST | 250 ppm 325 mg/m3 | USA. NIOSH Recommended Exposure Limits |
| Potential for | dermal absorption | |
| TWA | 200 ppm 260 mg/m3 | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| The value in | mg/m3 is approxir | mate. |

| STEL | 250 ppm 325 mg/m3 | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 |
|-----------|----------------------|-----------------------------------------------------------------------------------------------|
| Skin nota | tion | |
| TWA | 200 ppm 260 mg/m3 | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 |
| Skin nota | tion | |
| С | 1,000 ppm | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |
| Skin | | ••• |
| PEL | 200 ppm 260 mg/m3 | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |
| Skin | | ••• |
| STEL | 250 ppm 325 mg/m3 | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |
| Skin | | |

Biological occupational exposure limits

| Component | CAS-No. | Parameters | Value | Biological specimen | Basis |
|-----------|---------|----------------------------------------------------------|-----------------|---------------------|-------------------------------------------------|
| Methanol | 67-56-1 | Methanol | 15.0000 mg/l | Urine | ACGIH - Biological Exposure Indices (BEI) |
| | Remarks | End of shift (As soon as possible after exposure ceases) | | | |
| | | Methanol | 15 mg/l | Urine | ACGIH - Biological Exposure Indices (BEI) |
| | | End of shift (As soon as possible after exposure ceases) | | | |

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 30 min Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an

industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

| a) | Appearance | Form: liquid |
|----|----------------------------------------------------|----------------------------------------------|
| b) | Odour | No data available |
| c) | Odour Threshold | No data available |
| d) | рН | No data available |
| e) | Melting point/freezing point | Melting point/range: -87 °C (-125 °F) - lit. |
| f) | Initial boiling point and boiling range | 80 °C (176 °F) - lit. |
| g) | Flash point | 9.7 °C (49.5 °F) - closed cup |
| h) | Evaporation rate | No data available |
| i) | Flammability (solid, gas) | No data available |
| j) | Upper/lower flammability or explosive limits | No data available |
| k) | Vapour pressure | No data available |
| I) | Vapour density | No data available |
| m) | Relative density | 0.805 g/cm3 at 25 °C (77 °F) |
| n) | Water solubility | No data available |
| o) | Partition coefficient: n- octanol/water | No data available |
| p) | Auto-ignition temperature | No data available |
| q) | Decomposition temperature | No data available |
| r) | Viscosity | No data available |
| s) | Explosive properties | No data available |
| t) | Oxidizing properties | No data available |
| | her safety information data available | |

9.2

10. STABILITY AND REACTIVITY

- **10.1 Reactivity** No data available
- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** Vapours may form explosive mixture with air.
- **10.4** Conditions to avoid Heat, flames and sparks.
- **10.5** Incompatible materials Acids, Oxidizing agents, Alkali metals, Acid chlorides, Acid anhydrides, Reducing agents, Strong reducing agents
- Hazardous decomposition products
 Hazardous decomposition products formed under fire conditions. Carbon oxides
 Other decomposition products No data available
 In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity No data available

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation No data available

Serious eye damage/eye irritation No data available

Respiratory or skin sensitisation No data available

Germ cell mutagenicity

No data available

Carcinogenicity

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

Additional Information

RTECS: Not available

Methyl alcohol may be fatal or cause blindness if swallowed., Cannot be made non-poisonous., Effects due to ingestion may include:, Nausea, Dizziness, Gastrointestinal disturbance, Weakness, Confusion., Drowsiness, Unconsciousness, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence (Methanol) Liver - Irregularities - Based on Human Evidence (Ethyl methyl ketone)

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available

- **12.2 Persistence and degradability** No data available
- **12.3 Bioaccumulative potential** No data available
- **12.4 Mobility in soil** No data available
- **12.5 Results of PBT and vPvB assessment** PBT/vPvB assessment not available as chemical safety assessment not required/not conducted
- 12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1230 Class: 3 Proper shipping name: Methanol, solution Reportable Quantity (RQ): Packing group: II

Poison Inhalation Hazard: No

IMDG

| UN number: 1230 | Class: 3 (6.1) | Packing group: II | EMS-No: F-E, S-D |
|--------------------------------|----------------------|-------------------|------------------|
| Proper shipping name | : METHANOL, SOLUTION | I | |
| IATA UN number: 1230 | Class: 3 (6.1) | Packing group: II | |

UN number: 1230 Class: 3 (6.1) Proper shipping name: Methanol, solution

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

| The following components are subject to reporting levels establ | ished by SARA Title | III, Section 313: |
|---------------------------------------------------------------------------------|---------------------|-------------------|
| | CAŚ-No. | Revision Date |
| Methanol | 67-56-1 | 2007-07-01 |
| SARA 311/312 Hazards Fire Hazard, Acute Health Hazard, Chronic Health Hazard | | |
| Massachusetts Right To Know Components | | |
| 3 | CAS-No. | Revision Date |
| Methanol | 67-56-1 | 2007-07-01 |
| Pennsylvania Right To Know Components | | |
| · ······· | CAS-No. | Revision Date |
| Methanol | 67-56-1 | 2007-07-01 |
| Water | 7732-18-5 | |
| Ethyl methyl ketone | 78-93-3 | 1993-04-24 |
| New Jersey Right To Know Components | | |
| | CAS-No. | Revision Date |
| Methanol | 67-56-1 | 2007-07-01 |
| Water | 7732-18-5 | |
| California Prop. 65 Components | | |
| WARNING: This product contains a chemical known to the | CAS-No. | Revision Date |
| State of California to cause birth defects or other reproductive | 67-56-1 | 2012-03-16 |
| harm. | | |
| Methanol | | |

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

| Acute Tox. | Acute toxicity |
|---------------|--------------------------------------------------------|
| Flam. Liq. | Flammable liquids |
| H225 | Highly flammable liquid and vapour. |
| H301 | Toxic if swallowed. |
| H301 + H311 + | Toxic if swallowed, in contact with skin or if inhaled |
| H331 | |
| H311 | Toxic in contact with skin. |
| H331 | Toxic if inhaled. |
| H370 | Causes damage to organs. |
| STOT SE | Specific target organ toxicity - single exposure |

HMIS Rating

| Health hazard: | 2 |
|------------------------|---|
| Chronic Health Hazard: | * |
| Flammability: | 3 |
| Physical Hazard | 0 |
| | |

NFPA Rating

| Health hazard: | 2 |
|--------------------|---|
| Fire Hazard: | 3 |
| Reactivity Hazard: | 0 |
| | |

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 4.9

Revision Date: 09/23/2016

Print Date: 05/15/2018